




Recommended P.C.B Hole Layout

N=W/0 Post



W=With Post

Order Information:

ERYAY07BA-2.00-2-XX-PAxPCxPDxPB-G0-W-R

Pin Header Series

07BA: 2.00mm

Plastics Height:

1.50, 2.00 mm

Per Row: Double Layer

Pin: No. of Pins (02~80)

Size: PAxPCxPB

Plating:

G0=Gold Flash G1=1u" Gold G10=10u" Gold

G15=15u" Gold G30=30u" Gold

Post: W=With Post N=W/0 Post

Packing:

0=PE Bag A=Tray T=Tube

P=Tube+Cap R=Reel+Cap

Material:

Standard: PA6T Contact: Brass

Insulator: Polyester, UL94V-0

Electrical Characteristics:

Rated Current: 1.5AMP

Contact Resistance: 20mΩ Max

Withstand Voltage: 1000V AC/DC

Insulator Resistance: 1000MΩ Min

Mechanical

Operating Temperature: -40°C~+105°C

Dimension Antitheses List (mm)

ITEM	PA	PB	PC	PD	Plastic Height
Standard	4.00	1.27	6.60	3.40	2.00
Nonstandard	---	---	---	---	---

NINGBO ERYCO ELECTRONIC CO.,LTD



UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5
			CHK'D BY FENG
			APPR BY ZHAN

2.00mm Pin Header
Double Layer, Horizontal SMT, 2xN Pin

THIRD ANGLE PROJECTION




ERYAY07BA-2.00-2-XX-PAxPCxPDxPB-G0-W-R





Recommended P.C.B Hole Layout

Material:
 Standard: PA6T
 Contact: Brass
 Insulator: Polyester,UL 94 V-0
 Electrical Characteristics:
 Rated Current: 1.5AMP
 Contact Resistance: 20mΩ Max
 Withstand Voltage: 1000V AC/DC
 Insulator Resistance: 1000MΩ Min
 Mechanical
 Operating Temperature: -40°C~+105°C
 Max.Processing Temp:240°C for 30-60 seconds
 (260°C for 10 seconds)



Dimension Antitheses List (mm)				
ITEM	PA	PB	PC	Plastic Height
Standard	4.00	1.27	2.80	2.00
Nonstandard	---	---	---	---

Order Information:
 ERYAY07BA-2.00-1-XX-PAxPCxPB-G0-N-R



NINGBO ERYCO ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4			SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	THIRD ANGLE PROJECTION
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	

2.00mm Pin Header
 Single Layer,Horizontal SMT, 1xN Pin

ERYAY07BA-2.00-1-XX-PAxPCxPB-G0-N-R