

Material
 Screw:M2.5,Steel Zn plated
 Cage:Brass ,Nickel plated
 Pin Header:Brass, Tin plated
 Housing:PA66,UL94V-0
 Electrical
 Rated voltage: 300V
 Rated current: 16A
 Wire Range:22~12AWG 2.5mm²
 Contact Resistance: 20mΩ
 Insulation resistance: 500MΩ/DC500V
 Withstand voltage: AC2000V/1min
 Mechanical
 Temp.Range:-40℃~+105℃
 Soldering:250℃ 5Sec. Max.
 Torque:0.4Nm(3.54 Lb.in)
 Strip length:6~7mm

Order Information

ERYBY28- 5.00 -XXP-4 S XX

Terminal Block

Pitch

No : of Pole

Product Code:00~99
 Screw:S- Slot Screw
 C-cross Screw

Color: 4-Green

SECTION A-A

NINGBO ERYCO ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4			SCALE:---
0~3	3~18	18~50	50~120	
±0.12	±0.15	±0.3	±0.5	


DRWN BY PAN

CHK'D BY FENG

APPR BY ZHAN

Screw Conn Term Block 5.0mm

THIRD ANGLE PROJECTION



ERYBY28-5.00-XXP-4S