

Material

Housing: PA66, UL94V-0

Cage: Brass, Ni plated

Clamp: Phosphor bronze, Ni plated

Screws: M2.0, Steel, Zn plated

Electrical

Rated voltage: 300V

Rated current: 8A

Contact Resistance: 20 mΩ

Insulation resistance: 500MΩ/DC500V

Withstand voltage: AC2000V/1min

Wire Range: 28~16AWG 1.0mm<sup>2</sup>

Mechanical

Temp. Range: -40°C~+105°C

Strip length: 6~7mm

Torque: 0.2Nm (1.7Lbin)

Order Information

ERYBYDKFFM-5.08-XXP-4S00

Terminal Block

Pitch

No. of Pole

Color: 4-Green

Screw: S-Slot Screw C-Cross Screw

Product Code: 00~99

NINGBO ERYCO ELECTRONIC CO.,LTD

UNITS:mm

SHEET SIZE: A4

SCALE: ---

DRWN BY PAN

Pluggable Terminal Block 5.08 MM

0~3

3~18

18~50

50~120

CHK'D BY FENG

THIRD ANGLE PROJECTION

ERYBYDKFFM-5.08-XXP-4S-00


±0.12

±0.15

±0.3

±0.5

APPR BY ZHAN



1

2

3

4

5

6

7

8

9