



**ELECTRICAL**

1. Rating: 20mA 12VDC
2. Contact Resistance:  $\leq 50\Omega$  max (Initial)
3. Insulation Resistance:  $\geq 100M\Omega$  min (DC 250V)
4. Dielectric Strength: AC 250V (50/60Hz For 1 minute)
5. Electrically Life: 100000 Cycles
6. Environment Temperature:  $-25^{\circ}\text{C} \sim +70^{\circ}\text{C}$
7. Operating Force: 180~250 ( $\pm 30\text{gf}$ )
8. Seal Temperature:  $260^{\circ}\text{C} \sim 280^{\circ}\text{C}$

**ORDER INFORMATION**

ERYGYS4503-3.8-180

Series No \_\_\_\_\_  
 Height: 3.8mm, 4.8mm, 7.0mm, 8.5mm  
 Operating Force:  $180 \pm 30\text{gf}$

NINGBO ERYCO ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4			SCALE:---
0~3	3~18	18~50	50~120	
$\pm 0.12$	$\pm 0.15$	$\pm 0.3$	$\pm 0.5$	

DRWN BY PAN

CHK'D BY FENG

APPR BY ZHAN

4.5x4.5mm Tact Switch Series

THIRD ANGLE PROJECTION



ERYGYS4503